

machinebidder

ONLINE AUCTION SALE - ON BEHALF OF A
FINANCE COMPANY (170726)

(Ends: 22 Aug 2024)

ONLINE AUCTION SALE

On instructions received from a Finance Company

2 x Modern Multi Pallet CNC Machining Centres

Lot 1 MAZAK VARIAXIS i300 5 Axis AWC Vertical Machining Centre with Smooth Control . New 2018. Installed 2019 Capacity: Maximum workpiece dia.350mm. Maximum workpiece height 315mm. X axis stroke (saddle right/left movement) 350mm. Y axis stroke (column back/forth movement) 550mm. Z axis stroke (spindle up/down movement)510mm. A Axis travel (table tilt) 0.0001° x 1500000. C axis travel (table rotation) 0.0001° x 3600000. Maximum table load (evenly distributed) 60 kg. Spindle: Spindle taper 7/24 taper No.40. Spindle speeds 35-12,000 rpm. No. of simultaneous controlled axes 5

Lot 2 MATSUURA MX-330 10 Pallet 5 Axis Vertical Machining Centre with Matsuura G-Tech 31i Touch Screen Control. Year 2019. Installed 2022 Working surface 130mm dia. Capto C6 Pallet System. X/Y/Z travels 435mm/465mm/560mm. Travel A/C (degrees) -125~-10/360. Maximum work size 330mm dia. x 300mm high. Loading capacity 80 kg. Spindle taper BT 40. Spindle speeds 15,000 rpm. Renishaw RMP600 Spindle Inspection Probe. Renishaw Laser Broken Tool Detection System. Matsuura G-Tech 31i Touch Screen Control. Supplied new by Matsuura Machinery Ltd and installed in 2022.

Equipment has been removed for convenience of sale and are now located in Greater Manchester

Lot no.	Description
---------	-------------

machinebidder

Lot
no.

Description

1



MAZAK VARIAXIS i300 AWC 5 Axis Vertical Machining Centre with Smooth Control. New 2018. Installed 2019

Capacity: Maximum workpiece dia.350mm. Maximum workpiece height 315mm. X axis stroke (saddle right/left movement) 350mm. Y axis stroke (column back/forth movement) 550mm. Z axis stroke (spindle up/down movement)510mm. A Axis travel (table tilt) 0.0001° x 1500000. C axis travel (table rotation) 0.0001° x 3600000. Maximum table load (evenly distributed) 60 kg. Spindle: Spindle taper 7/24 taper No.40. Spindle speeds 35-12,000 rpm. Main motor (AC inverter motor) 40% ED rating 22 kW. Main motor (AC inverter motor) continuous rating 15 kW. Main motor maximum torque 143Nm. Feed Rates: Rapids X/Y/Z 60/60/56 m/min. A/C 18000 degrees/min. Cutting feed rate X/Y/Z 56000mm/min. No. of simultaneous controlled axes 5.

AWC (Automatic Workpiece Changer): No. of workpiece holders 32. Clamp interface HSK-A100. Maximum workpiece dia. 350mm. Maximum workpiece height 315mm. Workpiece holder mass 60 kg. Loader feedrate A axis (with workpiece) 9.5m/min (without workpiece 25m/min. Loader feedrate B axis 80m/min. Loader feedrate C axis 30m/min. Loader stroke A axis 299 °. Loader stroke A axis 950mm. No. of loading stations 1. No. of workpiece stocker stations including standby stations 34. ATC & Tool Magazine: Tool storage capacity 145. Tool selection method Fixed address, auto shorter path selection. Tool shank type BT40. Retention bolt type Yamazaki ANSI type. Maximum tool dia 90mm (with adjacent tool) . Maximum tool dia. 130mm (without adjacent tool). Maximum tool length (from reference face of taper) 350mm.Maximum weight of tool 8 kg. Maximum tool moment 6.5 Nm.

Coolant tank capacity 400 Litres.

Machine Dimensions L x W x H 4930mm x 3430mm x 2968mm.
Approximate weight 15,600 kg

Machine has been removed for convenience of sale and is now in storage in Greater Manchester

OFFERS ARE INVITED UNTIL 24 HOURS BEFORE THE AUCTION CLOSES

machinebidder

**Lot
no.**

Description

2



MATSUURA MX-330 10 Pallet 5 Axis Vertical Machining Centre with Matsuura G-Tech 31i Touch Screen Control. Installed 2022

Working surface 130mm dia. Capto C6 Pallet System. X/Y/Z travels 435mm/465mm/560mm. Travel A/C (degrees) -125~-10 /360. Maximum work size 330mm dia. x 300mm high. Loading capacity 80 kg. Spindle taper BT 40. Spindle speeds 15,000 rpm. Rapids X/Y/Z 40m/min. Rapid traverse A/C min-1 17/33. No of tools 90. Type of tool shank JIS B 6339 40T. Maximum tool dia. 60mm. Maximum tool weight 10kg. Tool changing time 1.1 seconds. FSE Swarf Management System (Side Exit) with Chip Bin. 20 Bar Through Spindle Coolant (Duplex filtration). Filtermist FX4000 including floor stand & F monitor. Renishaw RMP600 Spindle Inspection Probe. Renishaw Laser Broken Tool Detection System. Matsuura G-Tech 31i Touch Screen Control.

Complete with qty of Vices & Adapter Plates.

Selection of Toolholders.

Supplied new by Matsuura Machinery Ltd and installed in 2022.

Machine has been removed for convenience of sale and is now in storage in Greater Manchester

OFFERS ARE INVITED UNTIL 24 HOURS BEFORE THE AUCTION CLOSES
